



Sterisart® NF – 16469

System with Adapter for Prefilled Syringes



International pharmacopeias require the complete sterility of pharmaceutical products that are injected into the bloodstream or that otherwise enter the body below the skin surface. Manufacturers of such products are required to supply proof of the sterility of the final product batch.

The preferred method for sterility testing is the membrane filter method – any microorganism present is concentrated on the membrane filter surfaces in the sample containers. In the last step nutrient media are added to these containers and the containers are incubated under the conditions specified.

The Sterisart® NF system 16469 has been specifically designed for the sterility testing of liquids in prefilled syringes of various sizes (versions with and without needle). In addition, the system allows the exterior of needles attached to syringes to be sterility tested.

The special retainer on the double tubing system is used as an adapter for attaching prefilled syringes. The contents of these syringes are drained into the Sterisart® system and simultaneously mixed with rinsing solution that is drawn through a dual-needle metal spike. The liquid mixed in this manner is pumped in equal volumes into the two Sterisart® containers and filtered.

In the final step the culture media described by the pharmacopeias are pumped into these containers. The containers are subsequently incubated for two weeks, then evaluated.

The Sterisart® NF 16469 types are available as special isolator versions. The version with the suffix "gamma Septum"(or GSD) has a partitioned (i.e. septated) connector which allows sterile sampling during incubation avoiding a risk of contamination.

Ideally the systems are used in combination with the Sterisart® Universal pumps 16419 oder 16420. These can be used in clean rooms and clean benches or can be installed in isolators.

Sterisart® NF systems can also be used with other manufacturers' pumps which have been specially designed for disposable closed sterility testing systems. This requires an adapter to ensure the correct position of Sartorius NF units in the pumps of other manufacturers: 16412V (for older pumps) or 1ZG---0014 (for the latest pump versions).

Specifications

Pore size of the Sartochem® membrane filter	0.45 µm, tested with <i>Serratia marcescens</i>
Filter area	15.7 cm ² in each Sterisart® container
Flow rate (for water)	500 ml/min at 1 bar (approx. 15 psi)
Pore size of the air filters	0.2 µm PTFE, validated acc. to HIMA for the retention of <i>B. diminuta</i>
Sample container capacity	120 ml (graduation marks at 50, 75 and 100 ml)
Max. operating pressure	3 bar (approx. 44 psi) at 20 °C
Max. operating temperature	50 °C
Sterilization	gamma irradiation

Chemical compatibility of the components (24 hour contact at 20 °C)

	Sartochem® membrane	Tubing	Sterisart® containers
Aqueous solutions	compatible	compatible	compatible
Alcohols	compatible	compatible	compatible
Aliphatic hydrocarbons	compatible	compatible	compatible
Oils	compatible	compatible	compatible
Salt solutions	compatible	compatible	compatible
Ether	compatible	compatible	compatible
Weak acids	compatible	compatible	limited compatibility
Weak bases	limited compatibility	compatible	limited compatibility
Aromatic hydrocarbons	compatible	not compatible	not compatible
Esters	compatible	not compatible	limited compatibility
Halogenated hydrocarbons	compatible	not compatible	not compatible

Ordering information

Name	Description	Quantity	Order number
Sterisart® NF gamma	System with adapter for prefilled syringes (gamma sterilized, double-packed, optimal for use in isolators)	Box of 10	16469 GBD
Sterisart® NF gamma Septum	System with adapter for prefilled syringes and septum (gamma sterilized, double-packed, optimal for use in isolators)	Box of 10	16469 GSD
Sterisart® Universal pump	Basic version: Peristaltic pump for use with sample containers in sterility testing	1	16419
Sterisart® Universal pump	Upgraded version with display user software	1	16420
Pump adapters	For use with Sterisart® systems in older competitor pumps. Please clarify pump type used.	2	16412 V
Pump adapters	For use with Sterisart® systems in newer competitor pumps. Please clarify pump type used.	1	1ZG---0014

Further Sterisart® units and accessories are available on request.

Comprehensive validation support literature is available on request.
Publ. No. SL-4507-e

Sartorius Stedim Biotech GmbH
August-Spindler-Strasse 11
37079 Goettingen, Germany
Phone +49.551.308.0
Fax +49.551.308.3289
www.sartorius-stedim.com
USA Toll-Free +1.800.368.7178
UK +44.1372.737159
France +33.442.845600
Italy +39.055.63.40.41
Spain +34.90.2110935
Japan +81.3.3740.5407

Specifications subject to change without notice. Printed and copyrighted by Sartorius Stedim Biotech GmbH | W
Publication No.: SLD2006-e12015
Order No.: 85030-521-06
Ver. 01 | 2012