



arium® 613CPM4-----V

Reverse Osmosis Modules



Description

The arium® 613CPM4-----V reverse osmosis modules are designed for installation within the arium® RO 61316 and the arium® EDI 61215 systems. The arium® RO modules consist of two self-contained membrane-housings engineered for easy installation and reliable service. Each module contains a low energy thin film composite RO membrane (TFC) enclosed in a polypropylene housing. Each housing contains feed, permeate and concentrate water connections with internal flow control for membrane rinsing.

Features and Benefits

The arium® RO modules are designed to produce up to 380 liters* per day of RO permeate water. The low-energy TFC membranes require less energy (pressure) to produce a higher quantity of water/hour than comparable membranes of the same size. This reduces running cost by consuming less electric power.

The RO modules typically produce greater than 50% permeate recovery, which conserves water while still providing 99% or greater salt rejection.

Each time the systems shuts down with a full tank, the RO membranes are back-flushed with permeate water. Back-flushing with RO permeate water removes particles and potential scale forming salts from the membrane surface, promoting longer service life and reducing system maintenance. This back-flushing operation allows the RO membranes to be stored in RO permeate water instead of feed or mains water between service operations, which extends the service life of the membrane. At startup, the system will produce higher quality permeate water as compared to conventional systems that store membranes in feed water.

The product water is ideally suited for use as feed water to a Type 1 lab water system (e.g. arium® 611) or other device requiring pretreated water.

Specifications

RO membranes:	low-energy polyamide thin-film composite
---------------	--

Housing:	Polypropylene
----------	---------------

Unit Dimensions

Height:	30.8 cm (12.13")
---------	------------------

Diameter:	7.8 cm (3.07")
-----------	----------------

Operation Weight

468 g (1.03 lbs) each

Feed Pressure

Min:	1.2 bar 15 psi
------	------------------

Max:	6.8 bar 100 psi
------	-------------------

Temperature:	5°C–35°C (41°F–99°F)
--------------	-------------------------

Silt Density Index:	< 3
---------------------	-----

Iron (Total as Fe):	< 0.1 ppm
---------------------	-----------

Hardness (max CaCO ₃):	360 ppm or softened water
------------------------------------	---------------------------

Output

Up to 380 liters per day* (up to 16 liters per hour) at 25°C ± 20%

Ordering Information

Order number:	613CPM4-----V
---------------	---------------

Quantity:	2 modules
-----------	-----------

* depends on feed water quality and temperature

Sartorius Stedim Biotech GmbH
August-Spindler-Strasse 11
37079 Goettingen, Germany
Phone +49.551.308.0
Fax +49.551.308.3289
www.sartorius-stedim.com

USA Toll-Free +1.800.368.7178
UK +44.1372.737159
France +33.442.845600
Italy +39.055.63.40.41
Spain +34.91.3586102
Japan +81.3.3740.5407

Specifications subject to change without notice. Printed and copyrighted by Sartorius Stedim Biotech GmbH
W/sart-000 · G
Publication No.: SLG2040-e08105
Order No.: 85030-532-40